

Technical note N°1/2024

### Class Rules update

Following the last 2 measurement checks done in Lanzarote, the following numbers will be updated in the next version of the CR:

#### E.3 Keel

E.3.6 (a)	maximum bulb weight	2085kg	
E.3.6 (b)	Fin weight	minimum 131kg	maximum 134kg
	Fin weight with 4 bolts and washers but without TT		
	Corrector weight (made of lead) shall be installed on the top of the fin head.		

#### F.3 Mast

F.3.5 (a)	Mast weight	minimum 143kg	maximum 146kg
F.3.5 (b)	Mast center of gravity from MDP		minimum 6500mm

### Class Rules housekeeping

#### C.2.3 HELMSMAN LIMITATIONS

The helmsman shall be designated an Owner, Substitute or Charter helmsman (the category).

In fleet racing series one Owner, Charter or Substitute helmsman shall steer the boat at all times. There is no driver limitation for formats other than fleet racing, including match races and exhibition races. These formats shall be approved by the CO.

#### C.4.1 MANDATORY

(a) The boat shall be equipped with personal buoyancy for each crew member to the minimum standard EN 393: 1995 (CE 50 N), or near equivalent. It is recommended that buoyancy as per WS Offshore Special Regulations - **Appendix B** or inshore races EN 396 ISO 12402 (150 N) be carried on board. Automatic inflatable personal buoyancy is not permitted, except where equipped with hydrostatic inflator system.

#### C.6.1 MANDATORY

The boat shall be equipped to the minimum standard set out in the WS Offshore Special Regulations - **Appendix B, with the following modifications:**  
At point b) ... with a minimum content weight (or equivalent) of 2 kg.  
At point i) ... if equipped with a combustion engine.

#### C.7.3 CORRECTOR WEIGHTS

**(c) For boats equipped with electric engine, the total corrector weights can exceed the limit set above. The distribution of such weights can be different according to the CM indications.**

App H – Hydraulic system

1	Forestay ram, HCL-10B or HCL.II-10/B black anodizes cylinder - Reckmann
1	HCP11C, Control panel – Reckmann, max pressure 440 Bars for HCL-10B cylinder and 350 Bars for HCL.II-10/B cylinder

App H – Running rigging specifications

PBO cover is allowed for Main sheet, jib sheets and Spinnaker sheets,  
Minimum diameter for the Spinnaker sheets is 7mm,